NATIONAL DISTRIBUTOR OF QUALITY MAINTENANCE SUPPLIES SINCE 1958 1-800-558-2808

Start an Order

MY ACCOUNT | SERVICES | PDF CATALOG | CHARTS | MSDS | NEW PRODUCTS | ABOUT US | CONTACT US | HELP

Home > Products > Chemicals & Paint > MSDS Sheets > MSDS 6583 -- [Back]

LOGIN
Login E-mail:
Password:
GO
Apply for an account! »

PRODUCT SEARCH
GO
Advanced Search »

- All Products
- Fasteners
  - » Grade 8
  - » Grade 5
  - » Threaded Fasteners
- Hardware
- Rivet & Rivet Guns
- Vehicle Lighting
- Electrical Products
- Tubing & Tube Fittings
- Air Brake Products
- Hose & Hose Ends
- Cutting Tools
- Abrasives
- Safety Products & Welding Supplies
- Chemicals & Paint
  - » MSDS Information
  - » CA/OTC Information
- Shop Supplies
- Vehicle Parts & Accessories
- Assortments & Steel Equipment
  - » Assortment Listing

- Online Catalog Index
- Discontinued & Overstock Specials

Printer-Friendly View

MSDS 6583

6583: Rescue 911 Leak Sealer 18 Oz [12]
MSDS Last updated: 07/01/2005

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174.

IDENTIFY AND MANUFACTURER'S INFORMATION
NFPA Rating: Health - 3; Flammability- 2: Reactivity- 0: Special- 0
HMIS Rating: Health- 3: Flammability- 2: Reactivity- 0: Personal Protection-B

Manufactured For: RED ROSE
Address: 4550 Ziebart Place
Las Vegas, NV 89103

DOT Hazard Classification: ORM-D
Identity (trade name as used on label): Rescue 911 Roof Patch, Black

Date Prepared: 09/15/2003 Prepared By; BB

MSDS Number; 961 Revision-1

Information Calls: (702) 736-6500
EMERGENCY RESPONSE NUMBER: 1(800)255-3924

NOTICE; JUDGMENT BASED ON INDIRECT TEST DATA

SECTION 1- MATERIAL IDENTIFICATION AND INFORMATION

COMPONENTS Chemical Names And Common Names	CAS #	SARA III List	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref.Source**
(Hazardous Components 1% or greater: Carcinogens 0.1% or greater)					
Hydrocarbon Propellant	68476-86-8	No	800	800	d
Dichloromethane	75-09-2	Yes	500	25	a.b.c.
n-Tallowalkyl Trimethylene Diamines Ole.	61791-53-5	No	N/E	N/E	d
Petroleum Asphalt	N/E	No	N/E	N/E	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: N/A Specific Gravity (H20=1); Concentrate Only = 1.0773
Vapor Pressure: PSIG @ 70 F (Aerosols): N/D
Vapor Pressure (None-Aerosols) (mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/D
Evaporation Rate (= 1): N/E
Solubility in Water: Nil
Water Reactive: No
Appearance and Odor: Black Asphalt

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA

Explosive Limit (Product): Lower - 1.0 Upper - 6.0
Flash Point and Method Used (TOC): Level 2
Extinguisher Media: Foam, dry chemical, carbon dioxide, water.
Special Fire Fighting Procedures: Use water spray to cool fire exposed surfaces and to protect personnel. Isolate "fuel" supply from fire. Avoid spraying water directly into storage containers due to danger of boil over. This liquid is volatile and gives off invisible vapors. Either the liquid or vapor may settle in low areas or travel some distance along the ground or surface to ignition

sources where they may ignite or explode.
Unusual Fire & Explosion Hazards: Contents under pressure. Do not expose aerosols to temperatures above 130 F. or the container may rupture.

SECTION 4 - REACTIVITY HAZARD DATA

Stability [X]Stable [ ]Unstable
Hazardous Polymerization [ ]Will [X]will not occur
Incompatibility (Mat. To avoid): Strong oxidizers
Conditions to Avoid: Open flame, welding arcs. Heat.
Hazardous Decomposition Products; Carbon monoxide, carbon dioxide.

SECTION 5 - HEALTH HAZARD DATA

Primary Routes of Entry: [X] Inhalation [ ] Ingestion [X] Skin Absorption
[ ] Eye [ ] Not Hazardous
Acute Effects:
Inhalation: Excessive inhalation may produce symptoms of central nervous system depression, ranging from light-headedness, nausea and vomiting, to unconsciousness and death.
Eye Contact: An irritant of the eyes, causing pain, acclimation and general inflammation.
Skin Contact: Mildly irritating to the skin. Skin contact may produce a burning sensation-prolonged or repeated contact may cause skin to become reddened, rough, and dry due to the removal of natural oils and may result in dermatitis.
Ingestion: May cause irritation of the gastrointestinal tract with vomiting. If vomiting results in aspiration, chemical pneumonia may follow. Absorption through the gastrointestinal tract may product symptoms of central nervous system depression ranging from light headedness to unconsciousness.
Chronic Effects: Can cause headache, mental confusion, depression, fatigue, loss of sense of balance, and visual disturbances. Excessive exposures may cause cardiac arrhythmias,Carboxyhemoglobinemia, liver and kidney effects.
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.

EMERGENCY FIRST AID PROCEDURES
Eye Contact: Irrigate with flowing water immediately and continuously for 15 minutes. Consult medical personnel.
Skin Contact: Wash off in flowing water or shower.
Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.
Ingestion; DO NOT INDUCE VOMITING. Call a physician and/or transport to emergency facility immediately. NOTE TO PHYSICIAN; Because rapid absorption may occur through lungs if aspirated and cause systemic effects, the decision of whether to induce vomiting or not should be made by a physician. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighted against toxicity when considering emptying the stomach. Exposure may increase "myocardial irritability". Do not administer sympathyoinetic drugs unless absolutely necessary.

SECTION 6 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (specify type): Based on contamination level and working limits of the respirator, use a respirator approved by NIOSH/MSHA.
Eye Protection; Face shield and goggles or chemical goggles should be worn.
Protective Gloves: Impervious gloves should be worn. Gloves contaminated with product should be discarded. Poly fluorinated polyethylene has been suggested.
Ventilation Requirements: Use adequate level exhaust ventilation. Note: Where carbon monoxide may be generated, special ventilation may be required. Local exhaust recommended when appropriate to control employee exposure.
Other Protective Clothing & Equipment: Standard work clothing. Standard work shoes; discard if shoes cannot be decontaminated. Store contaminated clothing in well ventilated cabinets or closed containers. Wash contaminated clothing and dry before reuse.
Hygienic Work Practices: Avoid contact with skin and avoid breathing vapors. Do not eat, drink or smoke in work area. Wash hands prior to eating, drinking or using restroom.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Container Is Punctures And Material Is Spilled Or Released: Clean up area by mopping or with absorbent materials and place in closed container for disposal. Consult Federal, State, and Local disposal authorities.
Waste Disposal Methods: Consult local authorities for proper waste disposal procedures. Empty, de-pressurized containers cannot be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.
Precautions To Be Taken In Handling & Storage: When utilizing pressurized

containers follow standard safety practices for handling aerosols. Do not puncture or incinerate containers. Do not store at temperatures above 130 F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.
Other Precautions & or Special Hazards: KEEP OUT OF REACH OF CHILDREN.
Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only.

The information contained in this MSDS was obtained from current and reliable sources, however, the data is provided without any warrenty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of Imperial Supplies LLC, Imperial will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this MSDS shall be created or inferred by any statement in this MSDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this MSDS. The user is responsible for full compliance.

For more product information by email, click here

Imperial Supplies LLC does not provide services and products outside the United States

Home | My Account | Print Catalog | On-line Catalog | New Products | Imperial Services | Charts | Contact Imperial | About Imperial
Conditions of Use | Warranty | Opt Out | Career Opportunities | Request Info | Downloads | Privacy Policy | Links | Site Map | HELP!

© 2008 Imperial Supplies LLC Questions or comments? Contact us.