



# Safety Data Sheet

Revision Date: 10/03/2018

## SECTION 1: Identification and Company Details

**Product Name:** 2001 Felt-Backed Sheet Vinyl Tile Adhesive  
**Product Code:** 2001  
**Manufacturer/ Supplier:** Roberts Canada Ltd.  
**Address:** 34 Hansen Road S.  
Brampton, ON L6W 3H4  
**Phone:** (905) 791-4444 9am-5pm EST  
**Emergency Phone:** 1(888) 226-8832 (CANUTEC) 24 hour response  
**Recommended Use:** Adhesive

## SECTION 2: Hazard(s) Identification

**Classification of the substance or mixture:** This product is not classified as hazardous under GHS criteria.

## SECTION 3: Composition / Information on Ingredients

	<u>Weight %</u>	<u>CAS #</u>
Naphthenic Oil	6%	64741-96-4
Urea	2%	57-13-6
Quartz	0.30%	14808-60-7
Titanium Dioxide	0.50%	13463-67-7

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding. During normal usage of the product as recommended, airborne dusts will not be present.

## SECTION 4: First-Aid Measures

**Inhalation:** Move victim to fresh air. Consult physician if necessary.  
**Skin Contact:** Wash with soap and water. Remove contaminated clothing. Consult physician if necessary.  
**Eye Contact:** Flush with copious amounts of water for at least 15 minutes. Consult physician if necessary.  
**Ingestion:** Do not induce vomiting. Wash mouth with water. Consult physician.  
**Note to Physician:** **Eyes:** Stain for evidence of corneal injury. If cornea is burned, instill antibiotic steroid preparation.  
**Skin:** Treat symptomatically as for contact dermatitis or thermal burns. If burned, treat as thermal burn.  
**Ingestion:** Treat symptomatically. There is no specific antidote. Inducing vomiting is contraindicated because of the irritating nature of this compound. **Respiratory:** Treatment is essentially symptomatic. Remove individual with symptoms from exposure and assist in breathing if necessary.

## SECTION 5: Fire-Fighting Measures

**Extinguishing Media:** This product is not flammable. Use fire- extinguishing media appropriate for surrounding materials.  
**Hazardous Combustion Products:** No particular hazards known.  
**Protection of Firefighters:** Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

## SECTION 6: Accidental Release Measures

**Personal Precautions:** Use protective gloves, goggles and suitable protective clothing.  
**Environmental Precautions:** Do not allow product to get into drains, soil, or surface water.  
**Methods of Clean-up:** Small Spillages: Absorb with sand or other inert absorbent. Large Spillages: Dam and absorb spillages. Collect spillage in containers, seal securely and deliver for disposal according to local regulations. Wear necessary protective equipment.

## SECTION 7: Handling and Storage

**Handling Precautions:** Provide good ventilation. Do not use in confined spaces without adequate ventilation and/or respirator. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product.  
**Storage:** Keep separate from food, feedstuffs, fertilizers and other sensitive material. Store in closed original container at temperatures between 5°C and 30°C/ 40°F and 86°F. Protect from freezing and direct sunlight.

## SECTION 8: Exposure Control / Personal Protection

**Exposure Guidelines:** Not determined  
**Engineering Controls:** Provide adequate ventilation.  
**Personal Protective Equipment:**  
***Skin Protection*** - Permeation resistant gloves (butyl rubber, nitrile rubber, PVC or polyvinyl alcohol).  
***Eye/Face Protection*** - Glasses with side shields, chemical splash goggles and/or face shield.

<u>Chemical Name / CAS No.</u>	<u>OSHA Exposure Limits</u>	<u>ACGIH Exposure Limits</u>	<u>Other Exposure Limits</u>
Naphthenic Oil/64741-96-4	Not Established	Not Established	Not Established
Urea/ 57-13-6	Not Established	Not Established	Not Established
Quartz/ 14808-60-7	Not Established	0.025 mg/m <sup>3</sup> (respirable fraction)	NIOSH: 0.05 mg/m <sup>3</sup> TWA (respirable dust)
Titanium Dioxide/ 14808-60-7	15 mg/m <sup>3</sup> TWA (total dust)	10 mg/m <sup>3</sup> TWA	Not Established

## SECTION 9: Physical and Chemical Properties

**Appearance:** Heavy beige paste  
**Odor:** Very mild, non- offensive odor  
**Relative Density:** 1.2  
**Odor Threshold:** Not available  
**Solubility:** Miscible in water  
**pH:** 9.2-9.8  
**Partition Coefficient:** n-octanol/water; Not determined  
**Melting Point:** Not determined  
**Freezing Point:** Not determined  
**Auto-ignition Temperature:** Not determined  
**Flash Point:** Non- flammable > 204 C (400 F) Cleveland Closed Cup  
**Decomposition Temperature:** Not determined  
**Evaporation Rate:** Not determined  
**Viscosity:** Not determined  
**Flammability (Solid/Gas):** Not applicable  
**Upper/Lower Flammability:** Not determined  
**VOC Content:** 18 g/L  
**Vapor Pressure:** Not Determined  
**Boiling Point:** 100°C/ 212°F

## SECTION 10: Stability and Reactivity

**Chemical Stability:** Stable under normal temperature conditions and recommended use.  
**Conditions to Avoid:** Excessive heat, direct sunlight and/or frost.  
**Materials to Avoid:** None.

**SECTION 11: Toxicological Information**

Mixture Toxicity: Inhalation Toxicity LC50: 98 mg/L

**Acute toxicity:**

Ingestion: Not determined  
Inhalation: Not determined  
Skin Contact: Not determined

	<u>CAS Number</u>	<u>%Weight</u>
Titanium Dioxide	13463-67-7	0.5
Quartz	14808-60-7	0.3

**SECTION 12: Ecological Information**

**Mobility and Bioaccumulation Potential:** Not determined

**Degradation:** Not determined

**Aquatic Toxicity:** Not determined

**LC50 – 24 hour (Static):** Not determined

**Component Ecotoxicity:** Naphthenic Oil

96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L

48 Hr EC50 Daphnia magna: >1000 mg/L

Urea

96 Hr LC50 Poecilia reticulata: 16200 - 18300 mg/L

48 Hr EC50 Daphnia magna: 3910 mg/L [Static]

**SECTION 13: Disposal Considerations**

**Disposal:** Dispose of waste and residues in accordance with local authority requirements. Incineration is the preferred method of disposal.

**Wastes or Residues:** Same as above.

**SECTION 14: Transport Information**

**Road:** DOT Proper Shipping Name: **Non-Regulated**  
DOT Packing Group: N/A  
DOT Label: N/A  
UN Number: N/A

**Ocean:** Proper Shipping Name: **Non-Regulated**  
Sea – IMO/IMDG Class: N/A  
UN Number: N/A  
Label: N/A  
Packing Group: N/A  
Marine Pollutant: N/A  
EMS: N/A

**Air:** Proper Shipping Name: **Non-Regulated**  
Air – ICAO/IATA Class: N/A  
UN Number: N/A  
Label: N/A  
Sub Class: N/A  
Packing Group: N/A  
Pack Instr. Passenger: N/A

**SECTION 15: Regulatory Information**

**Status on Substance Lists:** The concentrations shown in this document are maximum levels (weight %) to be used for regulations.

**TSCA:** The components of this product are contained on the chemical substance inventory list  
**IARC:** Not carcinogenic  
**OSHA PEL's** None

**Federal EPA:** Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA): Requires notification of the national response center of release of quantities of hazardous substances equal to or greater than the reportable quantities (RQ's) in 40 CFR 302.4. Components present in this product at level which could require reporting under the statute are:

Chemical Name	CAS Number	% by Weight	RQ
None	None	None	None

Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III: Sections 301-304 require emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQ) in 40 CFR 355. Components present in this product at level which could require reporting under this statute are:

Chemical Name	CAS Number	% by Weight	RQ
None	None	None	None

Section 311-312 require products be reviewed and applicable EPA Hazard Definitions be identified and made known.

**NJ RTK**

- 13463-67-7 Titanium Dioxide
- 14808-60-7 Quartz
- 1332-58-7 Inert Filler

**Pennsylvania RTK**

- 13463-67-7 Titanium Dioxide
- 14808-60-7 Quartz
- 1332-58-7 Inert Filler
- 8050-09-7 Rosin

**SARA 302** Extremely Hazardous Substances - None

**Massachusetts RTK**

- 13463-67-7 Titanium Dioxide
- 14808-60-7 Quartz
- 1332-58-7 Inert Fill

**EPA Hazard Classifications:**

Acute	Chronic	Fire	Pressure	Reactive
Hazard	Hazard	Hazard	Hazard	Hazard
<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>	<b>No</b>

Section 313 requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313). This information must be included in all SDSs that are distributed for this material. Components present in this product at level which could require reporting under the statute are: **None**

**Canada DSL:** All components are on the DSL list or exempt.

**California Proposition 65:** Does not contain any listed chemical to the best of our knowledge.

**SECTION 16: Other Information**

This Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Hazardous Products Regulation (WHMIS 2015)

**HMIS RATING: HEALTH-1, FLAMMABILITY-0, REACTIVITY-0, PERSONAL PROTECTION- B.**

Prepared by: Roberts Product Safety & Regulatory Compliance Group,

The information herein is given in good faith, but no warranty expressed or implied is made. Roberts urges users of this product to evaluate its suitability and compliance with local regulations as Roberts cannot foresee the final use of the product, nor the final location of usage.

Date of issue: 10/03/2018