

VISTA PAINT CORPORATION -- PROFORMER -- 8010-00N019426

===== Product Identification =====

Product ID:PROFORMER
MSDS Date:04/10/1990
FSC:8010
NIIN:00N019426
MSDS Number: BLGPZ
=== Responsible Party ===
Company Name:VISTA PAINT CORPORATION
Address:2020 E ORANGETHORPE AVE
City:FULLERTON
State:CA
ZIP:92631
Country:US
Info Phone Num:714-680-3800
Emergency Phone Num:714-680-3800
CAGE:0C4T4
=== Contractor Identification ===
Company Name:VISTA PAINT CORP
Address:2020 E ORANGETHORPE AVE
Box:City:FULLERTON
State:CA
ZIP:92631
Country:US
Phone:714-680-3800
CAGE:0C4T4

===== Composition/Information on Ingredients =====

Ingred Name:ING 6:CONTRAINDICATED EXCEPT FOR LIFE-SUSTAINING USED IN
HUMANS ACUTELY OR CHRONICALLY EXPOSED TO CHLOROCARBONS .
RTECS #:9999999ZZ

Ingred Name:FIRST AID PROC:& INTO FRESH AIR. IF BRTHG IS DFCLT, O*2
SHOULD BE ADMINSTERED BY QUALIFIED PERS. SEEK MD IMMED. (ING 9)
RTECS #:9999999ZZ

Ingred Name:ING 8:INGEST:SEEK EMER MED ATTN. THIS MATL IS SLIGHTLY TOX
BY INGEST & AN ASPIR HAZ. IF VICTIM IS DROWSY/UNCON (ING 10)
RTECS #:9999999ZZ

Ingred Name:ING 9:PLACE ON THE LEFT SIDE W/HEAD DOWN. DO NOT GIVE
ANYTHING BY MOUTH. IF VICTIM IS CONSCIOUS & ALERT, VOM (ING 11)
RTECS #:9999999ZZ

Ingred Name:ING 10:SHOULD BE INDUCED FOR INGEST OF LGE AMTS (MORE THAN
5 OZS IN AN ADULT) PREFERABLY W/SYRUP OF IPECAC UNDER(ING 12)
RTECS #:9999999ZZ

Ingred Name:ING 11:DIRECTION FROM A MD OR POIS CTR. IF SYRUP OF IPECAC
IS NOT AVAIL, VOM CAN BE INDUCED BY GENTLY PLACING (ING 13)
RTECS #:9999999ZZ

Ingred Name:ING 12:TWO FINGERS IN THE BACK OF THE THROAT. DO NOT LEAVE
VICTIM UNATTENDED.

RTECS #:9999999ZZ

Ingrid Name:EYE PROT:FULL LENGTH FACESHIELD MAY BE ADDED TO GOGGLES .
RTECS #:9999999ZZ

Ingrid Name:XYLENES (O-,M-,P- ISOMERS)(SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingrid Name:SILICA, CRYSTALLINE - CRISTOBALITE
CAS:14464-46-1
RTECS #:VV7325000
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.05 MG/M3 RDUST9293

Ingrid Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)
CAS:71-55-6
RTECS #:KJ2975000
OSHA PEL:350 PPM/450 STEL
ACGIH TLV:350 PPM/450STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingrid Name:SUPP DATA:VOM & CAUSE LUNG INFLAMM & DAM. ACUTE:MAY CAUSE
IRRIT, HDCH, NAUS, DIZZ, FATIGUE, LOSS OF COORDINATION (ING 5)
RTECS #:9999999ZZ

Ingrid Name:ING 4:OR UNCON. CHRONIC:NONE RECOGNIZED. CHLOROCARBON
MATERIALS HAVE PRDCE SENSIT OF THE MYOCARDIUM TO (ING 6)
RTECS #:9999999ZZ

Ingrid Name:ING 5:EPINEPHRINE IN LAB ANIMALS & COULD HAVE A SIMILAR EFT
IN HUMANS. ADRENOMIMETICS (E.G. EPINEPHRINE) MAY BE (ING 7)
RTECS #:9999999ZZ

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:YES OSHA:NO
Health Hazards Acute and Chronic:EYE:IRRITANT. DIRECT CONT W/THE LIQ OR
EXPOS TO VAP/MIST MAY CAUSE STINGING, TEARING, REDNESS & SWELL.
SKIN:MAY CAUSE IRRIT. PRLNGD/RPTD CONT MAY CAUSE REDNESS, BURNING &
DRYING & CRACKING. MAY BE ABSORBED THRU THE SKIN. CONT MAY RESULT IN
SKIN ABSORP BUT SYMPS OF TOX ARE NOT ANTICIPATED BY THIS ROUTE (SEE EFTS
OF OVEREXPOSURE)
Explanation of Carcinogenicity:CRYSTALLINE SILICA. IARC - GROUP 2A
Effects of Overexposure:HLTH HAZ:ALONE UNDER NORM CONDITNS OF USE.
INHAL:BRTHG HIGH CONC OF VAP/MIST MAY CAUSE IRRIT OF THE
NOSE/THROAT. SIGNS OF NERV SYS DEPRESS (E.G. DROW, DIZZ, LOSS OF
COORDINATION & FATIGUE). INGEST:EXCESSIVE QTY'S MAY CAUSE IRRIT OF
THE DIGESTIVE TRACT. SIGNS OF NERV SYS DEPRESS (E.G. DROW, DIZZ,

LOSS OF (SEE SUPP DATA)
Medical Cond Aggravated by Exposure:PERSON W/PRE-EXISTING SKIN
DISORDERS & RESPIRATORY SYMPTOMS ASSOC W/PRE-EXISTING LUNG
DISORDERS (E.G. ASTHMA-LIKE CONDITION) MAY BE AGGRAVATED TO
EXPOSURE TO THIS MATERIAL.

===== First Aid Measures =====

First Aid:EYE:MOVE VICTIM AWAY FROM EXPOS TO VAP & INTO FRESH AIR. IF
IRRIT/REDNESS DEVELOPS, SEEK MD. FOR DIRECT CONT, HOLD EYELIDS
APART & FLUSH W/CLEAN WATER FOR AT LEAST 15 MINS. SEEK MD. SKIN:
REMOVE CONTA MD CLTHG. CLEANSE THORO BY WASH W/MILD SOAP & WATER.
IF IRRIT OR REDNESS DEVELOPS & PERSISTS, SEEK MD. INHAL:IF
RESP/OTHER SYMPS OF EXPOS DEVELOP, MOVE VICTIM AWAY FROM SOURCE OF
EXPOS (SEE INGRED 8)

===== Fire Fighting Measures =====

Flash Point Method:TCC
Flash Point:106F,41C
Lower Limits:1.0%
Upper Limits:6.0%
Extinguishing Media:WATER SPRAY, FOAM, CARBON DIOXIDE OR DRY CHEMICAL.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRVD PRESS DEMAND SCBA &
FULL PROT EQUIP . FULL STREAM WATER MAY BE UNSUITABLE AS EXTING
METH, BUT IS HELPFUL IN KEEPING (SEE SUPP DATA)
Unusual Fire/Explosion Hazard:DO NOT APPLY TO HOT SURF. KEEP AWAY FROM
HEAT, SPARKS & OPEN FLAME. DO NOT STORE/MIX W/STRONG OXIDANTS. KEEP
CONTRS TIGHTLY CLSD. CLSD CONTRS (SEE SUPP DATA)

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILTION. SOAK UP W/
DIATOMACEOUS SILICA & PICK UP W/SHOVEL. VAPOR IS HEAVIER THAN AIR &
MAY TRAVEL A CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION &
FLASHBACK.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTRS CLSD WHEN NOT IN USE. DO
NOT STORE/HNDL NEAR HEAT, FLAMES, SPARKS & STRONG OXIDANTS. STORE
IN COOL, WELL VENTD AREA.AVOID BRTHG VAPS.
Other Precautions:ROTATE STOCK, USE OLDER MATLS FIRST. INSPECT FOR
LEAKS IN ALL CONTRS. NO SMOKING IN AREA OF USE. DO NOT USE IN THE
GEN VICINITY OF ARC WELDING, OPEN FLAMES OR HOT SURF. HEAT &/OR UV
RADIA MAY CAUSE TH E FORMATION OF HCL &/OR PHOSGENE .

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE A NIOSH/MSHA APPROVED RESPIRATOR IF TLV IS
EXCEEDED. EXAMPLE: TC-23C-436.
Ventilation:PROVIDE SUFFICIENT MECHANICAL VENTILATION W/EXPLOSION PROOF
EQUIPMENT TO MAINTAIN EXPOSURE LEVEL BELOW TLV/PEL.
Protective Gloves:IMPERVIOUS RUBBER GLOVES.
Eye Protection:CHEMICAL WORKERS GOGGLES.(SEE INGRED 14)
Other Protective Equipment:USE EYE WASH & SAFETY SHOWER. USE IMPERVIOUS

CLOTHING OR CHANGE CONTAMINATED CLOTHING IMMEDIATELY.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety and Health
FIRE FIGHT PROC:NEARBY CONTR COOL. AVOID SPREADING BURING LIQ W/WATER
USED FOR COOLING PURPOSES. EXPLO HAZ:MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT. THERMAL DECOMP PRODS MAY INCL HCL & PHOSGENE . EFTS
OF OVEREXP:COORDINATION & FATIGUE). ASPIR HAZ - THIS MATL CAN ENTER
LUNGS DURING SWALLOWING OR (SEE INGRED 4)

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:314F,157C
Vapor Pres:2.0
Vapor Density:>1
Spec Gravity:1.2
Evaporation Rate & Reference:<1 (BUTYL ACETATE=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIQUID; MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING MATERIALS.
Stability Condition to Avoid:AVOID HEAT OR FLAME.
Hazardous Decomposition Products:CO2, CO, HCL, PHOSGENE, &
UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF ALL WASTE IN ACCORDANCE W/FEDERAL,
STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.