The Valvoline Company

Page 001

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

# CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Material Identity Product Name: HP GEAR OIL 85W-140 1/5 GA General or Generic ID: PETROLEUM BASED-LUBRICATING OIL

Company

Telephone Numbers

Emergency: 1-800-274-5263

The Valvoline Company P.O. Box 14000

Lexington, KY 40512

Information: 1-859-357-7206

COMPOSITION/INFORMATION ON INGREDIENTS

CAS Number % (by weight) Ingredient(s) 64742-65-0 87.0- 97.0 PETROLEUM DISTILLATES 2.8- 13.0 GEAR OIL ADDITIVE

## HAZARDS IDENTIFICATION

Potential Health Effects

Eye

Unlikely to cause eye irritation or injury.

Skin

Prolonged or repeated contact may dry and crack the skin. Additional symptoms of skin contact may include: allergic skin reaction (delayed skin rash which may be followed by blistering, scaling and other skin effects).

Swallowing

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful.

The Valvoline Company

Page 002

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

Inhalation

Breathing of vapor is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms of Exposure

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways), headache.

Target Organ Effects No data

Developmental Information

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Cancer Information

Based on the available information, this material cannot be classified with regard to carcinogenicity. This material is not listed as a carcinogen by the International Agency for Research on Cancer, the National Toxicology Program, or the Occupational Safety and Health Administration.

Other Health Effects No data

Primary Route(s) of Entry Inhalation, Skin contact, Eye contact, Ingestion.

## 4. FIRST AID MEASURES

Eyes

If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek medical attention.

The Valvoline Company

Page 003

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

Skin

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

Swallowing

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Note to Physicians

Preexisting disorders of the following organs ( or organ systems)

may be aggravated by exposure to this material: skin.

## 5. FIRE FIGHTING MEASURES

Flash Point > 300.0 F (148.8 C)

Explosive Limit
No data

Autoignition Temperature No data

Hazardous Products of Combustion

May form: aldehydes, alkyl mercaptans, carbon dioxide and carbon monoxide, hydrogen sulfide, nitrogen oxides, phosphorous oxides, sulfur oxides, toxic fumes, various hydrocarbons.

The Valvoline Company

Page 004

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

Fire and Explosion Hazards

Never use welding or cutting torch on or near drum (even empty)

because product (even just residue) can ignite explosively. Dense

smoke may be generated while burning.

Extinguishing Media regular foam, water fog, carbon dioxide, dry chemical.

Fire Fighting Instructions
Water or foam may cause frothing which can be violent and possibly
endanger the life of the firefighter. Wear a self-contained
breathing apparatus with a full facepiece operated in the positive
pressure demand mode with appropriate turn-out gear and chemical
resistant personal protective equipment. Refer to the personal
protective equipment section of this MSDS.

NFPA Rating Health - 1, Flammability - 1, Reactivity - 0

# 6. ACCIDENTAL RELEASE MEASURES

Small Spill

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

Large Spill

Prevent run-off to sewers, streams or other bodies of water. If
run-off occurs, notify proper authorities as required, that a
spill has occured. Persons not wearing protective equipment
should be excluded from area of spill until clean-up has been
completed. Stop spill at source, dike area of spill to prevent
spreading, pump liquid to salvage tank. Remaining liquid may be
taken up on sand, clay, earth, floor absorbent, or other absorbent
material and shoveled into containers.

### 7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or repeated contact.

Continued on next page

The Valvoline Company

Page 005 Date Prepared: 01/14/02 Date Printed: 04/26/07 MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

Storage

Keep containers closed when not in use. Do not store near high heat or open flames.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Eye Protection

Not required under normal conditions of use. However, if misting or splashing conditions exist, then safety glasses or chemical splash goggles are advised.

Skin Protection

Not normally required. However, wear resistant gloves such as nitrile rubber to prevent irritation which may result from prolonged or repeated skin contact with product.

Respiratory Protections

Not required under normal conditions of use. However, if oil mists are generated above recommended PEL/TLV of 5 mg/m3, then a NIOSH/MSEA approved respirator is advised in absence of proper environmental control. (See your industrial hygienist.)

Engineering Controls

Not required under normal conditions of use. However, if unusual operating conditions exist, then provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below PEL/TLV (s).

Exposure Guidelines Component \_\_\_\_\_

PETROLEUM DISTILLATES (64742-65-0) OSHA VPEL 5.000 mg/m3 - TWA Oil Mist ACGIH TLV 5.000 mg/m3 - TWA Oil Mist

GEAR OIL ADDITIVE No exposure limits established

The Valvoline Company

Page 006

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

9. PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (for component) > 425.0 F (218.3 C)

Vapor Pressure Not applicable

Specific Vapor Density No data

Specific Gravity
.906 @ 60.00 F

Liquid Density 7.550 lbs/gal 0 60.00 F .906 kg/l 0 15.60 C

Percent Volatiles (Including Water)
No data

Evaporation Rate No data

Appearance No data

State

LIQUID

Physical Form No data

Color

AMBER

Odor

PETROLEUM

Page 007 The Valvoline Company Date Prepared: 01/14/02 Date Printed: 04/26/07 MSDS No: 505.0173308-012.011 HP GEAR OIL 85W-140 1/5 GA рĦ Not applicable Viscosity - 27.0 cst ê 100 C 26.0 10. STABILITY AND REACTIVITY Hazardous Polymerization Product will not undergo hazardous polymerization. Hazardous Decomposition May form: aldehydes, alkyl mercaptans, carbon dioxide and carbon monoxide, hydrogen sulfide, nitrogen oxides, phosphorous oxides, sulfur oxides, various hydrocarbons. Chemical Stability Stable. Avoid heat, open flame, and prolonged storage at elevated temperatures. Incompatibility Avoid contact with: strong oxidizing agents. 11. TOXICOLOGICAL INFORMATION No data 12. ECOLOGICAL INFORMATION No data

## 13. DISPOSAL CONSIDERATION

Waste Management Information
Dispose of in accordance with all applicable local, state and federal regulations.

The Valvoline Company

Page 008

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

## 14. TRANSPORT INFORMATION

DOT Information - 49 CFR 172.101 DOT Description: Not Regulated

> Container/Mode: CASES/SURFACE - NO EXCEPTIONS

NOS Component: None

RQ (Reportable Quantity) - 49 CFR 172.101 Not applicable

#### 15. REGULATORY INFORMATION

US Federal Regulations

TSCA (Toxic Substances Control Act) Status
TSCA (UNITED STATES) The intentional ingredients of this
product are listed.

CERCLA RQ - 40 CFR 302.4 None

SARA 302 Components - 40 CFR 355 Appendix A None

Section 311/312 Hazard Class - 40 CFR 370.2 Immediate(X) Delayed() Fire() Reactive() Sudden Release of Pressure()

SARA 313 Components - 40 CFR 372.65 None

International Regulations

Inventory Status

AICS (AUSTRALIA) The intentional ingredients of this product are listed.

DSL (CANADA) The intentional ingredients of this product are listed.

ECL (SOUTH KOREA) The intentional ingredients of this product are listed.

ENCS (JAPAN) The intentional ingredients of this product are Continued on next page

The Valvoline Company

Page 009

Date Prepared: 01/14/02 Date Printed: 04/26/07

MSDS No: 505.0173308-012.011

HP GEAR OIL 85W-140 1/5 GA

listed.

PICCS (PHILIPPINES) The intentional ingredients of this product are listed.

State and Local Regulations California Proposition 65 None

### 16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.