

FRAZEE PAINT & WALL COVERINGS -- TRAFFIC PAINT WHITE, 5020700 -- 8010-00N022252

===== Product Identification =====

Product ID:TRAFFIC PAINT WHITE, 5020700
 MSDS Date:04/20/1989
 FSC:8010
 NIIN:00N022252
 MSDS Number: BLNZR
 === Responsible Party ===
 Company Name:FRAZEE PAINT & WALL COVERINGS
 Address:6625 MIRAMAR ROAD
 City:SAN DIEGO
 State:CA
 ZIP:92121
 Country:US
 Info Phone Num:619-276-9500
 Emergency Phone Num:619-276-9500
 Preparer's Name:ZEKE
 CAGE:FO493
 === Contractor Identification ===
 Company Name:FRAZEE INDUSTRIES INC
 Address:6625 MIRAMAR RD
 City:SAN DIEGO
 State:CA
 ZIP:92121
 Country:US
 Phone:858-626-3600
 CAGE:1GK99
 Company Name:FRAZEE PAINT & WALL COVERINGS
 Address:6625 MIRAMAR ROAD
 City:SAN DIEGO
 State:CA
 ZIP:92121
 Phone:(619) 276-9500
 CAGE:FO493

===== Composition/Information on Ingredients =====

Ingred Name:ETHANOL, 2-(2-BUTOXYETHOXY)-; (DIETHYLENE GLYCOL MONOBUTYL
 ETHER). VP:0 @ 68F.
 CAS:112-34-5
 RTECS #:KJ9100000
 Fraction by Wt: <5%

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)
 CAS:67-56-1
 RTECS #:PC1400000
 Fraction by Wt: 1%
 OSHA PEL:S,200PPM/250STEL
 ACGIH TLV:S,200PPM/250STEL; 93
 EPA Rpt Qty:5000 LBS
 DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.
 Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
 Health Hazards Acute and Chronic:INHAL:VAP/MIST CAN CAUSE HDCH,
 NAUS/IRRIT OF NOSE, THROAT/LUNGS. SKIN ABSORPTION:METHYL ALCOHOL IN
 PROD IS TOX BY SKIN ABSORPTION. EYES:IRRIT. INGEST:METHYL ALCOHOL
 IN PROD IS HIGHLY TOX BY INGEST. AS LITTLE AS 1 TO 4 OZ CAN BE
 FATAL OR RESULT IN PERMANENT INJURY SUCH AS BLINDNESS.

Explanation of Carcinogenicity:NOT RELEVANT
Effects of Overexposure:SEE HEALTH HAZARDS.
Medical Cond Aggravated by Exposure:OVEREXPOSURE TO VAPORS CAN CAUSE
NAUSEA, DIZZINESS AND HEADACHE.

===== First Aid Measures =====

First Aid:SKIN:CLEAN WITH SOAP AND WATER. GET MD ATTENTION.
INGEST:CONSULT MD IMMEDIATELY. INHAL:REMOVE TO FRESH AIR. CONSULT
MD. EYE:FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF IRRITATION
PERSISTS, GET MD ATTENTION.

===== Fire Fighting Measures =====

Lower Limits:5.5%
Upper Limits:36.5%
Extinguishing Media:FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICALS
AND WATER FOG.
Fire Fighting Procedures:FOLLOW RECOMMENDED PROCEDURES IN HANDLING FIRE
AREAS. WEAR ADEQUATE FIRE FIGHTING EQUIPMENT INCLUDING NIOSH/MSHA
APPROVED SCBA.
Unusual Fire/Explosion Hazard:POLYMER FILM CAN BURN. MATERIAL CAN
SPLATTER ABOVE 212F.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IMMEDIATELY AND SAFELY DISCARD
ABSORBENT. IN THE EVENT OF LARGE SPILLS, DIKE THE AREA AND PUMP THE
MATERIAL TO A PERMITTED WASTE TANK.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:USE WITH ADEQUATE VENTILATION. AVOID
PROLONGED BREATHING OF VAPOR. AVOID PROLONGED OR REPEATED SKIN
CONTACT. KEEP AWAY FROM EXCESSIVE HEAT.
Other Precautions:AVOID ALL SOURCES OF HEAT. USE GOOD PERSONAL HYGIENE
PRACTICES WHILE WORKING WITH THIS MATERIAL. DRY CONTAMINATED
CLOTHING BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WHEN SPRAYING MATL USE NIOSH/MSHA APPRVD
CARTRIDGE RESP/GAS MASK SUITABLE TO KEEP AIRBORNE MISTS/VAP CONC
BELOW TIME WEIGHTED THRESHOLD LIM VALUES. WHEN USING IN POORLY
VENT/CONFINED SPACES USE NIOSH/ MSHA APPRVD FRESH AIR RESP/SCBA.
Ventilation:MAINTAIN GOOD VENTILATION TO KEEP PRODUCT VAPOR
CONCENTRATIONS BELOW SPECIFIED TLV VALUES.
Protective Gloves:IMPERVIOUS GLOVES .
Eye Protection:CHEMICAL WORKERS GOGGLES .
Other Protective Equipment:TO PREVENT REPEATED OR PROLONGED SKIN
CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.
Work Hygienic Practices:EYE WASHES & SAFETY SHOWER IN WORKPLACE ARE
RECOMMENDED, AS WELL AS BARRIER CREAMS. DAILY SHOWERS & CHANGE OF
CLOTHES.
Supplemental Safety and Health
NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:212F,100C
Vapor Pres:SEE ING
Vapor Density:>1
Spec Gravity:1.7

Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:DILUTABLE
Appearance and Odor:WHITE VISCOUS LIQUID WITH A MILD ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID MATERIALS THAT ARE WATER REACTIVE. ALSO AVOID STRONG ALKALINE AND
ACIDIC SUBSTANCES.
Stability Condition to Avoid:HEAT MAY CAUSE CONTAINERS TO RUPTURE.
AVOID TEMPERATURES BELOW 40F. AVOID FREEZING CONDITIONS.
Hazardous Decomposition Products:CO, CO2 ON COMBUSTION.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS CURRENTLY IN FORCE FOR THIS PRODUCT HAZARD
CLASS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.